



HXH330 High Speed Injection Molding Machine

Technical Parameter :

MODEL:HXH 330			
TECHNICAL PARAMETER TABLE			
INJECTION UNIT	SCREW DIAMETER	mm	55
	SCREW L/D RATIO	L/D	24
	INJECTION CAPACITY (THEORETICAL)	cm ³	582
	INJECTION WEIGHT(PS)	g	529
	INJECTION PRESSURE	MPa	185
	SCREW SPEED	rpm	310
CLAMPING UNIT	CLAMP FORCE	KN	3300

Ningbo Jiangdong HYSION Machinery Co., Ltd.

Address: No.36 Yongjiang South Road, Beilun District, Ningbo, Zhejiang, China

Tel: +86-574-27858986

Fax: +86-574-27858980

E-mail: haixiongmac@gmail.com gewaicun@163.com



HYSION 海雄机械

PLASTIC INJECTION MOLDING MACHINE

	OPEN STROKE	mm	625
	MAX. MOULD	mm	650
	MIN. MOULD	mm	250
	SPACE BWTWEEN TIE-BARS (W×H)	mm	720×670
	EJECTOR FORCE	KN	125
	EJECTOR STROKE	KN	180
OTHERS	PUMP PRESSURE	MPa	16
	MOTOR POWER	KW	30*2
	HEATING POWER	KW	20.3
	MACHINE DIMENSION (L×W×H)	m	7.02*1.77*2.18
	MACHINE WEIGHT	t	13
Special Specification :			
1.Proportional direction valve for mold opening and closing			
2.Single cylinder injection			
3.Infrared ray heating			

Ningbo Jiangdong HYSION Machinery Co., Ltd.

Address: No.36 Yongjiang South Road, Beilun District, Ningbo, Zhejiang, China

Tel: +86-574-27858986

Fax: +86-574-27858980

E-mail: haixiongmac@gmail.com gewaicun@163.com